



| diamètre vis | Longueur fileté L / (code) | | | | | | | | | | | | | Epaisseur mini tôle | Ø trou | T | distance mini trou bord de tôle |
|--------------|-----------------------------|-------|-------|-------|--------------|--------------|-------|----|-------|----|-------|--------------|----|---------------------|----------------|-------|---------------------------------|
| | 6 | 8 | 10 | 12 | 15 | 18 | 20 | 22 | 25 | 28 | 30 | 35 | 40 | | | | |
| | | | | | | | | | | | | | | | +0.08 -0.00 | ±0.25 | |
| M2x0.4 | | 11526 | | | | | | | | | | | | 1.0 | 2.0 | 3.5 | 4.8 |
| M2.5x0.45 | * | * | * | 41256 | <i>11524</i> | <i>11525</i> | | | | | | | | 1.0 | 2.5 | 4.1 | 5.4 |
| M3x0.5 | 11527 | 11528 | 11529 | 11530 | 11532 | 11534 | 11535 | * | 32134 | | 44195 | | | 1.0 | 3.0 | 4.6 | 5.6 |
| M4x0.7 | 11536 | 11537 | 11538 | 11539 | <i>11541</i> | 11543 | 11544 | * | 12532 | * | 31922 | * | * | 1.0 | 4.0 | 5.9 | 7.2 |
| M5x0.8 | | 40037 | 11545 | 11546 | 11548 | 11550 | 11551 | * | 11552 | * | * | 28827 | * | 1.0 | 5.0 | 6.5 | 7.2 |
| M6x1.0 | | * | 11555 | 11556 | 16448 | 08803 | 23968 | * | 17574 | * | 26320 | <i>26321</i> | * | 1.6 | 6.0 | 8.2 | 7.9 |
| M8x1.25 | | * | * | * | 11557 | 08681 | 08714 | * | 26323 | | 26324 | <i>26325</i> | * | 2.4 | 8.0 | 9.6 | 9.6 |
| M10x1.5 | | | | | | | | | | | | | | 2.4 | 10.0 | 13.94 | 13.4 |

* sur demande

italique : nous consulter pour les délais d'approvisionnement.